Fujitsu recommends Windows® 7.

Data Sheet
Fujitsu ESPRIMO E900 0-Watt Desktop PC

The Innovative 0-Watt PC

The new Fujitsu ESPRIMO E900 0-Watt PC, equipped with highly innovative technology from Fujitsu and Intel®, is a power-saving wonder which fully meets all business and space requirements. With a volume of less than 13 liters it can be positioned vertically or horizontally - ideal for every desk. Made of specially selected material and, in addition to the 0-Watt function, equipped with further power-save options, such as a switched monitor outlet and power management, the Fujitsu ESPRIMO small form factor PC already meets today the legal requirements of tomorrow. Furthermore, this desktop PC, equipped with a power supply with an efficiency of up to 94%, more than meets all the environmental guidelines. Don't make any compromises!

0-Watt PC
Cost savings by completely reducing off-mode losses
- Patented function for 0 Watt power consumption in off mode with simultaneous management in a time slot that can be optionally set

Zero noise PC
Pleasant working environment due to completely quiet system (solid state disk required)
- Fan stop in standard operations

Environmentally conscious product with ENERGY STAR® certification
Your contribution to environmental protection for the continued existence of our planet
- Halogen-free printed circuit mainboard and power supply, sophisticated product concept for the entire lifecycle

Highest energy efficiency coupled with intelligent performance
The best-in-class regarding power consumption combined with new levels of performance
- State-of-the-art Intel® Core™ processors with Turbo Boost and hyperthreading technology, a switched monitor outlet and a power supply with up to 94% efficiency

System management
Simple system administration for complex IT infrastructures
- Intel® vPro™ technology (depending on CPU)

Fujitsu recommends Windows® 7.

Components

	Intel® vPro™ Logo with Intel® Core i5-2400, Intel® Core™ i5-2500 and Intel® Core™ i7-2600 processors.
Processor	Intel® Core™ i7-2600 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2100 processor (2 Cores / 4 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Pentium® processor G840 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G620 (2 Cores / 2 Threads, 2.60 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G530 (2 Cores / 2 Threads, 2.40 GHz, 2 MB)
Operating system	
Operating system	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP Citrix XenClient™ 2
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SSD SATA, 128 GB, 2.5-inch
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 320 GB, 3.5-inch
	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch
Hard disk notes	Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300 LP, 512 MB
	NVIDIA® GeForce® GT 420
	NVIDIA® GeForce® 405 display port low profile, 512 MB
	LFH59/ 2x DVI-I adapter cable
	LFH59/ 2x DP adapter cable
	DP to DVI-D (single link) Adapter Cable
	2nd NVIDIA® Quadro® NVS 300 LP, 512 MB
Drives (optional)	Blu-ray Disc™ Triple Writer
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 20in1, USB 2.0, 3.5-Inch
	MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch

Interface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only)
	USB 3.0 PCIe x1
	Parallel Interface
	Gigabit Ethernet PCIe x1, DS
	eSATA Interface
	Dual serial card PCIe x1, powered
	Dual serial card PCIe x1
Base unit	ESPRIMO E900 0-Watt
Mainboard	
Mainboard type	D3062
Formfactor	ATX
Chipset	Intel® Q67
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	6
thereof SATA III	2
thereof eSATA	2 (optional)
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI Raid 1/0
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	14
USB 3.0 total	optional
USB front	4
USB rear	8
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)

Interfaces	
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality
Input device / components	
	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO
Drive bays	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"
Slots	
PCI-Express 2.0 x16	1 x (200 mm) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (200 mm) Low profile
PCI-Express x1	1 x (174 mm) Low profile
PCI (32-bit / 33 MHz)	1 x (174 mm) Low profile
Slots optional configuration	or 2x PCI full high via Riser
Graphics on board	
Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
Graphics features	Dual display support DirectX 10.1 HDCP support OpenGL® 2.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)

Graphics on board	
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 91% / 94% / 92%
	0-Watt mode automatically
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched
Power consumption	
Power consumption note	See white paper Energy Consumption 0-Watt mode automatically
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=862c8e0b-983d-43c5-aeca-85429f85d6ef
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD, ODD)	
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load (Blue angel requirement)	4.0 B/ 26 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	SSD: no noise emmision; 2,5" HDD: 3.4 B/ 17 dB(A); 3,5" HDD: 3.4 B/ 19 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.8 B/ 23 dB(A)
Noise Operation mode 4: High load	3.8 B/ 23 dB(A)
Noise Operation mode 5: Office applications 2.0	SSD: no noise emmision; 2,5" HDD: 3.4 B/ 17 dB(A); 3,5" HDD: 3.4 B/ 19 dB(A)
Idle mode (Blue Angel requirement)	SSD: no noise emmision; 2,5" HDD: 3.4 B/ 17 dB(A); 3,5" HDD: 3.4 B/ 19 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	340 x 382 x 98 mm
Operating position	Vertical / horizontal (optional, feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C
Compliance	
Product	ESPRIMO E900
Model	DT8-3062
Germany	Blauer Engel / Blue Angel TÜV GS
Europe	CE Nordic Swan
USA/Canada	FCC Class B cCSAus

Compliance	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® Gold (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Additional Software	
Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)
Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime
Compatibility (references)	
	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 7.0
Manageability software	DeskView 10.x client management including:
DeskView components	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu
Security	
System protection	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
Audit proof protection	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces

Fujitsu recommends Windows® 7.

Security	
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

Serviceability	
	EasyFix EasyChange for HDD EasyChange for optical drives

Packaging information	
Packaging dimension	467x265x540 mm
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (g) EPS / PS	180 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty	
Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)

Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO E900 0-Watt, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E900 0-Watt, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2011-09-30 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions